



# Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

## 1 Identification

- **Product identifier**
- **Trade name: Wax And Grease Remover**
- **Product code:** SBWG
- **Recommended use and restriction on use**
- **Recommended use:** Pre-Cleaner prior to painting in professional automotive shops.
- **Restrictions on use:**  
Product is for use by professionally trained painters only. Not for use by the general public.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Bayou Innovations, LLC dba UreChem Paints  
38 South Park Drive  
Perkinston, MS 39573  
601-928-4143  
info@urechem-paints.com
- **Emergency telephone number:**  
ChemTel  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flam. Liq. 2 H225 Highly flammable liquid and vapor.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  
  
GHS02 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**  
H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.

(Cont'd. on page 2)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 1)

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing mist, vapors, or spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards**

This product is a component mixed with other products for use. When mixed with other products, mixtures will have hazards of all components. Refer to other component SDS for additional hazards of ready for use mixtures.

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Components:**

64742-49-0	Naphtha (petroleum), hydrotreated light	<85%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
64742-89-8	Solvent naphtha (petroleum), light aliphatic	<85%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	<85%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
67-63-0	Propan-2-ol	≤10%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Eye Irrit. 2A, H319; STOT SE 3, H336</li> </ul>	
111-65-9	Octane	<10%

(Cont'd. on page 3)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 2)

	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
142-82-5	<p>Heptane</p> <ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	<10%

**Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

## 4 First-aid measures

**Description of first aid measures**

**After inhalation:**

Supply fresh air.  
 Provide oxygen treatment if affected person has difficulty breathing.  
 If experiencing respiratory symptoms: Call a doctor.  
 In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If skin irritation continues, consult a doctor.

**After eye contact:**

Remove contact lenses if worn.  
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

Rinse out mouth and then drink plenty of water.  
 Do not induce vomiting; immediately call for medical help.  
 A person vomiting while lying on their back should be turned onto their side.

**Most important symptoms and effects, both acute and delayed:**

Breathing difficulty  
 Coughing  
 Dizziness  
 Headache  
 Causes skin and eye irritation.  
 Gastric or intestinal disorders when ingested.  
 Nausea in case of ingestion.  
 Disorientation  
 Unconsciousness

**Danger:**

May be fatal if swallowed and enters airways.  
 Danger of impaired breathing.

**Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.  
 If swallowed or in case of vomiting, danger of entering the lungs.  
 If necessary oxygen respiration treatment.  
 Later observation for pneumonia and pulmonary edema.  
 If medical advice is needed, have product container or label at hand.

(Cont'd. on page 4)



## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 3)

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
  - Alcohol resistant foam
  - Carbon dioxide
  - Fire-extinguishing powder
  - Gaseous extinguishing agents
  - Water fog / haze
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
  - Highly flammable liquid and vapor.
  - Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
  - Wear self-contained respiratory protective device.
  - Wear fully protective suit.
- **Additional information:**
  - Use large quantities of foam as it is partially destroyed by the product.
  - Cool endangered containers with water fog.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
  - Particular danger of slipping on leaked/spilled product.
  - Wear protective equipment. Keep unprotected persons away.
  - Ensure adequate ventilation.
  - Keep away from ignition sources.
  - For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions**
  - Do not allow to enter sewers/ surface or ground water.
  - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
  - Towel or mop up material and collect in a suitable container.
  - For large spills, absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
  - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

### 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
  - Avoid splashes or spray in enclosed areas.
  - Use only in well ventilated areas.

(Cont'd. on page 5)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 4)

- Avoid contact with the eyes and skin.
- Avoid breathing mist, vapors, or spray.
- Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
  - Highly flammable liquid and vapor.
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Flammable gas-air mixtures may be formed in empty containers/receptacles.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
  - Avoid storage near extreme heat, ignition sources or open flame.
  - Store in cool, dry conditions in well sealed receptacles.
- **Information about storage in one common storage facility:**
  - Store away from foodstuffs.
  - Store away from oxidizers, strong acids, strong bases.
- **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**67-63-0 Propan-2-ol**

PEL (USA)	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV (USA)	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE

**111-65-9 Octane**

PEL (USA)	Long-term value: 2350 mg/m <sup>3</sup> , 500 ppm n-Octane only
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 75 ppm Ceiling limit value: 1800* mg/m <sup>3</sup> , 385* ppm *15 min
TLV (USA)	Long-term value: 1401 mg/m <sup>3</sup> , 300 ppm
EL (Canada)	Long-term value: 300 ppm
EV (Canada)	Short-term value: 1750 mg/m <sup>3</sup> , 375 ppm Long-term value: 1400 mg/m <sup>3</sup> , 300 ppm

(Cont'd. on page 6)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 5)

LMPE (Mexico) | Long-term value: 300 ppm

**142-82-5 Heptane**

PEL (USA)	Long-term value: 2000 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 85 ppm Ceiling limit value: 1800* mg/m <sup>3</sup> , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m <sup>3</sup> , 500 ppm Long-term value: 1635 mg/m <sup>3</sup> , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

**· Ingredients with biological limit values:****67-63-0 Propan-2-ol**

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

**· Exposure controls****· General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

**· Engineering controls:** Provide adequate ventilation.**· Breathing equipment:**

Suitable respiratory protective device recommended.  
NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**· Eye protection:**

Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

**· Body protection:** Protective work clothing**· Risk management measures** No relevant information available.

(Cont'd. on page 7)



## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Wax And Grease Remover

(Cont'd. of page 6)

### 9 Physical and chemical properties

**Information on basic physical and chemical properties****Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Organic solvent
Odor threshold:	Not determined.

pH-value:	Not determined.
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	82.8-150 °C (181-238 °F)

Flash point: 14.4 °C (57.9 °F)

Flammability (solid, gaseous): Not applicable.

Auto-ignition temperature: Not determined.

Decomposition temperature: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**Explosion limits**

Lower:	0.9 Vol %
Upper:	12 Vol %

Oxidizing properties: Non-oxidizing.

Vapor pressure: Not determined.

**Density:**

Relative density:	0.76
Vapor density:	>1
Evaporation rate:	Not determined.

**Solubility in / Miscibility with**

Water:	Insoluble. Partly miscible.
--------	--------------------------------

Partition coefficient (n-octanol/water): Not determined.

**Viscosity**

Dynamic:	10 mPas
Kinematic:	Not determined.

Other information: No relevant information available.

### 10 Stability and reactivity

- Reactivity:** No relevant information available.
- Chemical stability:** Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- Possibility of hazardous reactions**

(Cont'd. on page 8)



## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 7)

Used empty containers may contain product gases which form explosive mixtures with air.

Highly flammable liquid and vapor.

Reacts violently with oxidizing agents.

Toxic fumes may be released if heated above the decomposition point.

· **Conditions to avoid** Excessive heat.· **Incompatible materials**

Oxidizing agents.

Strong acids and alkali.

· **Hazardous decomposition products**

Under fire conditions only:

Carbon monoxide and carbon dioxide

Hydrocarbons

### 11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:** Based on available data, the classification criteria are not met.· **LD/LC50 values that are relevant for classification:** None.· **Primary irritant effect:**· **On the skin:** Irritant to skin and mucous membranes.· **On the eye:** Causes serious eye irritation.· **Sensitization:** Based on available data, the classification criteria are not met.· **IARC (International Agency for Research on Cancer):**

Present in trace quantities.

71-43-2	Benzene	1
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B

· **NTP (National Toxicology Program):**

Present in trace quantities.

71-43-2	Benzene
91-20-3	Naphthalene

· **OSHA-Ca (Occupational Safety & Health Administration):**

Present in trace quantities.

71-43-2	Benzene
---------	---------

· **Probable route(s) of exposure:**

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.· **Carcinogenicity:** Based on available data, the classification criteria are not met.· **Reproductive toxicity:** Based on available data, the classification criteria are not met.· **STOT-single exposure:** May cause drowsiness or dizziness.· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.· **Aspiration hazard:** May be fatal if swallowed and enters airways.

(Cont'd. on page 9)





# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Wax And Grease Remover

(Cont'd. of page 8)



## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity** Toxic to aquatic life with long lasting effects.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Other adverse effects** No relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Contact waste processors for recycling information.  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, ADR/RID/ADN, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT, IATA</b>	Paint related material
· <b>ADR/RID/ADN, IMDG</b>	PAINT RELATED MATERIAL
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3
· <b>Label</b>	3
· <b>ADR/RID/ADN</b>	
	
· <b>Class</b>	3 (F1)
· <b>Label</b>	3

(Cont'd. on page 10)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 9)

· **IMDG, IATA**



- **Class** 3
- **Label** 3

- **Packing group**
- **DOT, ADR/RID/ADN, IMDG, IATA** II

- **Environmental hazards** Product contains environmentally hazardous substances: Heptane, Petroleum Distillates
- **Marine pollutant:**



Yes

- **Special precautions for user** Warning: Flammable liquids
- **Hazard identification number (Kemler code):** 33
- **EMS Number:** F-E,S-E

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

(Cont'd. on page 11)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 10)  
 Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 | Propan-2-ol

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Present in trace quantities.

71-43-2 | Benzene

91-20-3 | Naphthalene

100-41-4 | Ethylbenzene

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

Present in trace quantities.

71-43-2 | Benzene

· **Chemicals known to cause developmental toxicity:**

Present in trace quantities.

71-43-2 | Benzene

108-88-3 | Toluene

· **EPA (Environmental Protection Agency):**

142-82-5 | Heptane

D

· **IARC (International Agency for Research on Cancer):**

Present in trace quantities.

71-43-2 | Benzene

1

(Cont'd. on page 12)



## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

**Trade name: Wax And Grease Remover**

(Cont'd. of page 11)

91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B

**Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety &amp; Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

**Sources**Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtel.com](http://www.chemtel.com)