



AFE-52 Fisheye & Crater Eliminator

Description

AFE-52 is a blend of special polymers and solvent designed to lower the surface tension allowing solvent based paints to wet over common contaminants including silicones, waxes, grease, mold release agents and the like. As such, AFE-52 will eliminate or reduce “fisheyes” and craters present as a result of these common contaminants. Unlike other fisheye eliminators, AFE-52 is made from recoatable polymers allowing its use in primers, sealers, basecoats, and topcoats.



Components

- AFE-52 Fisheye & Crater Eliminator
- Any solvent based coating



Mixing Instructions

Mix your solvent based coating as you normally would per the manufacturers tech sheet then add ½ ounce (15 ml) of AFE-52 for every sprayable quart (32 ounces or 946 ml) of material just prior to use. Gently stir to avoid incorporating air.



Application

Apply as you normally would per the tech sheet for the two component polyurethane you are using. Turbo-Kure_{tm} has no effect on how the product sprays or handles on freshly mixed material.



Clean Up

Clean up as normally recommended for your solvent based coating recommendations. Because AFE-52 is made from recoatable polymers contamination of the wash solvent is not a concern unlike most other fisheye eliminators

Read MSDS of all components before using. Use proper personal protective equipment at all times. For use by professionally trained painters. **KEEP OUT OF REACH OF CHILDREN.** Bayou Innovations, LLC warrants that its products are free from defects at time of shipping. All other warranties and guaranties of any kind whether expressed or implied are disclaimed.